



IS-MP.2

The IS-MP.2 is a handheld reader for easy and efficient reading of RFID/NFC TAGs that are located closely together or positioned in areas that are difficult to access. The TAG information can be viewed directly on the OLED display, transferred via Bluetooth or read from the storage via USB.

TECHNICAL FEATURES



ATEX approval:
EX-zone 2/22
Ⓜ II 3G Ex ic IIC T4 Gc IP54
Ⓜ II 3D Ex ic IIIB T135°C Dc IP54



IECEx approval:
EX-zone 2/22
Ex ic IIC T4 Gc IP54
Ex ic IIIB T135°C Dc IP54



vibration feedback



size:
190 x 30 x 35 mm,
weight: 125 g



battery capacity
for 2.000 Bluetooth
readings



memory for
1000 readings



Bluetooth® 4.0 LE



OLED-display



1 ... 3 cm
reading distance



RFID/NFC tag-reader*:
LF 125kHz,
LF 134,2 kHz
FDX-B + HDX,
HF und NFC 13,56 MHz,
UHF 868 MHz



FURTHER FEATURES



IP54 certified



operation range from
-20 °C to 60 °C



real-time clock



apps with remote use
available

* = Allows individual configuration.

CONTENTS

IS-MP.2, USB cable, quick start manual and safety instructions

➤ Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. ➤ i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. ➤ © 2017 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | DW3170216